

USB to Serial Converter (RS485/RS422)

MC200



- RS485 (2-Wire), 2 Channels
- 115.2 kbps Data Rate
- Opto Isolation
- Internal Power Supply

USB to Serial Converter (RS485/RS422) MC200 Provides USB Port (Universal Serial Bus) that convert to isolated RS485 and RS422 that done not require PCI/ISA slots or IRQS. Simply plug the converter into an available USB port on your computer or hub. Windows will configure the converter as an additional COM Port, compatible with your Windows applications.

A pair of LEDs show when data is being received or transmitted. USB bus supplies power, so no separated power supply is needed. 2000 VAC of isolation.

Specifications

USB Interface

Compliance: USB 1.1/2.0

Connector: USB Type Mini-A (Female)

Speed: 12 Mbps (Full-Speed USB)

Class: CDC

USB Power: Low Power Device
(Draws < 100 mA)

Operating System:

Windows 10
Windows 10 x64
Windows 8.1
Windows 8.1 x64
Windows Server 2012
Windows 8
Windows 8 x64
Windows Server 2008 R2
Windows 7
Windows 7 x64
Windows Server 2008
Windows Server 2008 x64
Windows Vista
Windows Vista x64

Windows Server 2003

Windows Server 2003 x64

Windows XP

Windows XP x64

Serial Interface

Serial Standards:

RS485/422 (Isolated) 5 Pin Terminal Block,
2 Driver

Loading: RS485 Max 32 Unit

Distance: RS485/422 Length 1 Km.

Environmental Limits

Operating Temperature: 0 to 55 °C

Operating Humidity: 5 to 95% RH

Storage Temperature: 0 to 70 °C

Physical Characteristics

Dimension: W76 x H26 x D53 mm.

Warranty

Warranty Period: 1 Year

Ordering Information:

Example MC200

Package Checklist

1. MC200
2. USB Cable

การต่อใช้งาน MC200

